







# Twin needle/Three needle feed off the arm double chain stitcher

DA-9270

DA-9280

- Sew attractive balloon stitches onto thin materials, without puckering (9270)
- A tractor-type presser foot can be used to easily ride over thick sections. (9280)




Narrow cylinder bed feed off-the-arm double chain stitchers Ideal for a wide range of materials from shirts to jeans

## **High-quality sewing**

## Attractive balloon stitches

Low-tension sewing gives an attractive finished appearance to balloon stitches. It also produces pliant seams and prevents puckering.



## Movable needle guards requires no adjustment

A movable needle guard has been adopted in order to prevent skipped stitches from occurring. The movable needle guard timing and feed mechanism timing are fully coordinated, so that no adjustment is necessary even if the stitch length is changed. (It may be required to readjust the position of the movable needle guard according to materials and threads.)



## Workability is also greatly improved

## Handles small cylindrical articles too

The outer diameter of the cylinder is a slim 171 mm, with extra consideration given to the ease of use by the operator.



### Full pushbutton operation

The stitch length can be changed simply by pressing a button while turning the machine pulley to align the scale marks.



## **Options**


#### **Needle thread cooler**

The needle thread cooler cools the needle thread using silicon oil in order to prevent thread breakages due to heat.



#### **Chain cutter**

Cuts the thread at the same time as the sewing end is reached, providing increased work efficiency. 9270 (excepting fixed needle guard spec.) and 9280-C, -D spec. are available.



# **Specifications**

# DA-9270-

_						
	Applications		No. of needles		Needle gauge*	Needle
1	Light materials	2	2 needles		4.8 mm (3/16)	TV x 64 #12
	Light materials		2 Heedles	64	6.4 mm (1/4)	1 7 7 04 #12
2	Light-medium	2	2 needles		3.2 mm (1/8)	
	materials		2 Heedles	40	4.0 mm (5/32)	TV x 64 #14
	materials			48	4.8 mm (3/16)	
3	Medium materials	2	2 needles	64	6.4 mm (1/4)	TV x 64 #16
Α	Light materials	2	Oncodles	48	4.8 mm (3/16)	TV x 64 #11PSU
	Light materials, with puller		2 needles	64	6.4 mm (1/4)	1 V X 64 #11P5U
	with puller	3	3 needles	64	6.4 mm (1/4)	TV x 64 #11PSU

Lapper size					
M	Light materials				
L	Medium materials				
Н	Heavy materials				
Χ	Extra heavy materials				

<sup>\* 3-</sup>needle means total needle gauge



Applications			No. of needles	Needle gauge*		Needle	
5	Heavy materials	3 3 needles		64	6.4 mm (1/4)	TV x 5 #21	
7	Extra heavy	2	2 needles	64	6.4 mm (1/4)	TV x 5 #22	
	Materials (denim)	3	3 needles	64	6.4 mm (1/4)	TV x 5 #22	
С	Heavy materials, with puller	3	3 needles	64	6.4 mm (1/4)	TV x 5 #21	
D	Extra heavy	2	2 needles	64	6.4 mm (1/4)	TV x 5 #22	
	Materials (denim),	3	3 needles	64	6.4 mm (1/4)	TV x 5 #22	
	with puller		3 fieedies	80	8.0 mm (5/16)	1 1 1 2 3 #22	

Lapper size						
М	Light materials					
L	Medium materials					
Н	Heavy materials					
Χ	Extra heavy materials					

<sup>\* 3-</sup>needle means total needle gauge

		-	L	M	H	XH	<u> </u>	<b>→</b>  ←	D
Model	Double chain stitch	Bottom feed	Light materials	Medium materials	Heavy materials	Extra heavy materials	Height of presser foot	Stitch length	Max. sewing speed
DA-9270	*	*	*	*	-	-		For light materials 3.0 mm For medium materials 3.5 mm	4,000rpm
DA-9280	*	*	_	_	*	*	11 mm	4.2 mm	4,000rpm * (Normally 3,600 rpm)

<sup>\*</sup> The 9280 should normally be operated at a sewing speed of 3,600 rpm. When operating it at 4,000 rpm, the optional needle thread cooler should be fitted.

Product specifications are subject to change for improvement without notice. Please read instruction manual before using the machine for safety operation.



## **BROTHER INDUSTRIES, LTD.**

15-1,Naeshiro-cho,Mizuho-ku,Nagoya 467-8561, Japan. Phone:81-52-824-2177 Fax:81-52-811-7789 http://www.brother.com/





UKAS ENVIRONMENTAL	_		
ENVIRONMENTAL		ු යුතු,	
ENVIRONMENTAL	M .		
ENVIRONMENTAL	1	HIVAG	
		ENVIRONMENTAL MANAGEMENT	
6 091-C	6		

TURKEY To preserve environment, this catalog is produced using the ECF paper (Elemental Chlorine-Free) and SOY INK.

CHINA	BROTHER (CHINA) LTD.	+86-021-6237-1228
	http://www.brothergroup.com.cn/cn/area_top.html	
HONG KONG	BROTHER INTERNATIONAL (HK) LTD.	+852-3589-9040
	http://www.hrother.com.hk/	

**ASIA** BROTHER INTERNATIONAL SINGAPORE PTE LTD. +65-538-0311 http://www.brother.com.sa/

MIDDLE EAST BROTHER INTERNATIONAL (GULF) FZE +971-4-8835878 http://www.brother.ae/

**EUROPE** BROTHER INTERNATIONALE INDUSTRIEMASCHINEN G. m. b. H. +49-2822-6090 http://www.brother-ism.de

**AMERICA** BROTHER INTERNATIONAL CORPORATION +1-908-704-1700 http://www.brother-usa.com/

BROTHER INTERNATIONAL CORPORATION TURKISH LIAISON OFFICE +90-212-495-3971